
Bearing Box Process Specification and Tooling Design

Zhou Cong

Zhenjiang Zhongfu Ma Machinery Co., Ltd., Zhenjiang, China

Email address:

Congzhou2004@126.com

To cite this article:

Zhou Cong. Bearing Box Process Specification and Tooling Design. *International Journal of Mechanical Engineering and Applications*. Special Issue: *Bearing Box Process Specification and Tooling Design*. Vol. 8, No. 2, 2020, pp. 65-74. doi: 10.11648/j.ijmea.20200802.12

Received: March 15, 2020; **Accepted:** March 31, 2020; **Published:** May 14, 2020

Abstract: Reasonable process regulations and fixtures can ensure the high efficiency of parts processing and the economy of the enterprise. I started with data collection, then part analysis, then process design, then process specification design, and finally fixture design. In the process design, I obtained the best process route based on the experience of the production site to achieve the effect of saving time and increasing labor productivity. The design of the process specification was based on the production program, the production type was determined, and the process specification was compiled. Production, so the process card of parts and the card of machining process of parts were compiled. The fixture design is to design two sets of tools for the bearing box car mold and the bearing box drilling mold. The bearing box car mold is based on the processed large surface and the two right angle surfaces are used as positioning surfaces. The workpiece is fastened with bolts and nuts. The other large surface is up to size 70, $\phi 180H7$ holes; the bearing box drilling mold is based on the processed large surface, and is positioned at $\phi 180H7$ holes. The workpiece is fastened with bolts and nuts, and 6- $\phi 13$ holes are drilled to improve the part. Processing efficiency to ensure the quality of parts processing. In summary, the above-mentioned special fixture design scheme is adopted to ensure the production requirements of parts in batches and improve labor efficiency.

Keywords: Bearing Housing, Process Specification, Car Model, Drilling Die, Dimensional Accuracy, Positional Accuracy, Work Efficiency

1. Part Analysis

The bearing housing is the main part of the end jumper. The parts are made of HT200 gray cast iron for annealing treatment to ensure the mechanical strength and vibration damping of the parts. The structure of the parts is relatively complicated, so the cast blank is used.

1.1. Benchmark Selection

For parts, choose a non-machined surface as a rough reference. For workpieces with several unmachined surfaces, the unmachined surface with higher relative positional accuracy with the machining requirements should be used as the reference rough reference. The selection of the fine benchmark should mainly consider the problem of benchmark overlap. When the design basis and the process benchmark do not coincide, the size conversion should be performed [1]. When the part is machined, the machined large surface is used as the reference, and the two right angle surfaces are used as the positioning surface: the large surface limits 3 degrees of

freedom, and the two right angle surfaces limit 3 degrees of freedom. When drilling the part, the part is positioned with $\phi 180H7$ hole as the reference, and the two right-angled faces are used as the positioning surface: the large surface limits 3 degrees of freedom, the $\phi 180H7$ hole limits 2 degrees of freedom, and the right-angled surface limits 1 Degree of freedom.

1.2. Determine the Type of Production

The production program of the known parts is 120 pieces/year. Check the "Machinery Manufacturing Process and Equipment Design Manual" to determine that these parts are in the middle batch production.

1.3. Process Design Basis

Since the workpiece has an annual output of 120 pieces, it is a medium-volume production. Due to the complicated structure of the part, high dimensional accuracy and geometrical tolerance requirements, it is difficult to guarantee the dimensional accuracy and positional accuracy by ordinary

right-angled surfaces are used as the positioning surface, and the workpiece is fastened with bolts and nuts. The other large surface of the car reaches the size of 70, and the car is $\phi 180H7$ (see the process card 4) (C620 lying Lathe)

Step 7: Position the $\phi 180H7$ hole on the basis of the processed large surface, and fasten the workpiece with bolts and nuts, and drill 6- $\phi 13$ holes (see process card 5) (Z3050 radial drilling machine)

2.2. Part Blank Design (See Figure 3)




Figure 3. Part blank drawing.

2.3. Part Process Card Design

2.3.1. Process Card 1 (See Figure 4)

Mechanical processing card		Product number	part drawing number		Total 5 pages					
		product name	End jumper	part name	Bearing housing	page 1				
		workshop	employee ID	Process name	Material grade					
		metalworking	3	Milling	HT200					
		Blank type	Blank size	Pieces per blank	Pieces per unit					
		casting		1	6					
		Device name	Equipment model	device ID	Number of simultaneous machining					
		Vertical milling machine	X53							
		Fixture number	Fixture name	Coolant						
						Working hours				
						Quasi-final	Single			
Step number	Step content	Craft equipment		Spindle speed (rev / min)	Cutting speed (m / min)	Feed amount (mm / min)	Knife depth (mm)	Number of passes	Working hours quota	
Tracing	1 Straighten by line, mill a large surface with a roughness of 12.5 to size 75								Maneuver	auxiliary
Proofreading										
Basemap number										
Binding number										
		Establishment (date)		Review (date)	Working hours (date)	Countersigned (date)	Approved (date)			
mark	Number of pieces	Change the file number	signature	date	mark	Number of pieces	Change the file number	signature	date	

Figure 4. Parts Process Card 1.

2.3.2. Process Card 2 (See Figure 5)

Mechanical processing card										Product number	part drawing number			Total 6 pages		
										product name	End jumper		part name	Bearing housing	page 2	
										workshop	employee ID	Process name	Material grade			
										metalworking	4	Milling	HT200			
										Blank type	Blank size	Pieces per blank	Pieces per unit			
										casting		1	6			
										Device name	Equipment model	device ID	Number of simultaneous machining			
										Vertical milling machine	XS3					
										Fixture number	Fixture name	Coolant				
													Working hours			
													Quasi-final	Single		
Step number	Step content					Craft equipment					Spindle speed (rev / min)	Cutting speed (m / min)	Feed amount (mm / min)	Knife depth (mm)	Number of passes	Working hours quota
Tracing	1 Based on the processed large surface, milling the surface and grooves with a roughness of 12.5															
Proofreading																
Basemap number																
Binding number																
										Establishment (date)	Review (date)	Working hours (date)	Countersigned (date)	Approved (date)		
Mark	Number of pieces	Change the file number	signature	date	Mark	Number of pieces	Change the file number	signature	date							

Figure 5. Parts Process Card 2.

2.3.3. Process Card 3 (See Figure 6)

Mechanical processing card										Product number	part drawing number			Total 6 pages		
										product name	End jumper		part name	Bearing housing	page 3	
										workshop	employee ID	Process name	Material grade			
										metalworking	5	clamp	HT200			
										Blank type	Blank size	Pieces per blank	Pieces per unit			
										casting		1	6			
										Device name	Equipment model	device ID	Number of simultaneous machining			
										Rocker drilling	Z3050					
										Fixture number	Fixture name	Coolant				
													Working hours			
													Quasi-final	Single		
Step number	Step content					Craft equipment					Spindle speed (rev / min)	Cutting speed (m / min)	Feed amount (mm / min)	Knife depth (mm)	Number of passes	Working hours quota
Tracing	1 Drilling hole 2-φ21H7															
Proofreading																
Basemap number																
Binding number																
										Establishment (date)	Review (date)	Working hours (date)	Countersigned (date)	Approved (date)		
Mark	Number of pieces	Change the file number	signature	date	Mark	Number of pieces	Change the file number	signature	date							

Figure 6. Parts Process Card 3.

2.3.4. Process Card 4 (See Figure 7)

Mechanical processing card										Product number	part drawing number				Total 6 pages			
										product name	End jumper		part name	Bearing housing	page 4			
										workshop	employee ID	Process name	Material grade					
										metalworking	6	Turning	HT200					
										Blank type	Blank size		Pieces per blank	Pieces per unit				
										casting			1	6				
										Device name	Equipment model		device ID	Number of simultaneous machining				
Horizontal lathe		C620																
Fixture number			Fixture name		Coolant													
			Turning tooling															
					Working hours													
					Quasi-final													
					Single													
Step number	Step content				Craft equipment		Spindle speed (rev / min)	Cutting speed (m / min)	Feed amount (mm / min)	Knife depth (mm)	Number of passes	Working hours quota						
Tracing	1	Based on the processed large surface, with two right-angled surfaces as positioning surfaces. The nut tightens the workpiece, and the other large side of the car reaches the size 70, and the				Turning tooling												
Proofreading		180H7.																
Basemap number																		
Binding number																		
										Establishment (date)	Review (date)	Working hours (date)	Countersigned (date)	Approved (date)				
Mark	Number of pieces	Change the file number	signature	date	Mark	Number of pieces	Change the file number	signature	date									

Figure 7. Parts Process Card 4.

2.3.5. Process Card 5 (See Figure 8)

Mechanical processing card										Product number	part drawing number				Total 6 pages			
										product name	End jumper		part name	Bearing housing	page 5			
										workshop	employee ID	Process name	Material grade					
										metalworking	7	clamp	HT200					
										Blank type	Blank size		Pieces per blank	Pieces per unit				
										casting			1	6				
										Device name	Equipment model		device ID	Number of simultaneous machining				
Rocker drilling		Z3050																
Fixture number			Fixture name		Coolant													
			Drilling die															
					Working hours													
					Quasi-final													
					Single													
Step number	Step content				Craft equipment		Spindle speed (rev / min)	Cutting speed (m / min)	Feed amount (mm / min)	Knife depth (mm)	Number of passes	Working hours quota						
Tracing	1	Positioned with $\phi 180H7$ holes based on the processed large surface, using bolts and nuts workpiece, drill 6- $\phi 13$ holes				Drilling die												
Proofreading																		
Basemap number																		
Binding number																		
										Establishment (date)	Review (date)	Working hours (date)	Countersigned (date)	Approved (date)				
Mark	Number of pieces	Change the file number	signature	date	Mark	Number of pieces	Change the file number	signature	date									

Figure 8. Parts Process Card 5.

3. Fixture Design

3.1. Bearing Housing Model

The bearing housing has a complicated structure and an irregular shape. It is impossible to realize the machining of the hole and its end face without special tooling. For this reason, in the design of the tooling, the large surface of the workpiece has been used as the positioning reference, and the two right-angled surfaces of the workpiece are used as the positioning surface. The workpiece is fastened with bolts and nuts, and the auxiliary support is used to clamp the workpiece with the ejector pin. The large face is 70 in size and the car is $\phi 180H7$ [3].

3.1.1. Bearing Box Body Tooling Structure

The bearing box body tooling structure is shown in Figure 9. The bearing box body tooling is mainly composed of bottom plate, support plate, auxiliary support, ejector pin, support, bolt M20×90, nut M20, screw M20×100, bolt M10×60., nut M8, handle M8 and so on.




Figure 9. Bearing housing model.

- 1: Base plate 2: Support plate 3: Auxiliary support 4: Plunger 5: Support 6: Bolt M20×90
- 7: Nut M20 8: Screw M20×100 9: Bolt M10×60 10: Nut M8 11: Handle M8

3.1.2. Working Principle of Bearing Box Body Tooling

Place the bearing housing model on the four-jaw chuck of the C630 horizontal lathe, so that the end surface of the bottom plate fits on the end surface of the claw, adjust the claw to initially clamp the bottom plate of the tooling, and then use the table to find the end surface and outer circle of the bottom plate of the tooling, and then Clamp the bottom plate with four claws. The large surface of the workpiece has been machined on the bottom plate of the tooling, and the two right-angled faces of the workpiece are used as the positioning surface. The workpiece is fastened with bolts and nuts, and the auxiliary support is used to clamp the workpiece with the ejector pin. 70, car $\phi 180H7$ hole [4].

By using the self-designed bearing housing model, the other large surface of the bearing housing and the $\phi 180H7$ hole can meet the dimensional accuracy requirements of the drawings, ensure the consistency of mass production, solve the problem of low processing efficiency, and improve Work efficiency and various performance indicators [5].

3.1.3. Main Parts Design of Bearing Box Body Tooling

i. Backplane

The design of the bottom plate is shown in Figure 10. The part is connected with the workpiece, the support plate, the auxiliary support, the support, the screw and the bolt, and is the basic part of the tooling. The bottom plate material selects 45# medium carbon quenched and tempered structural steel, which has high strength and good machinability after quenching and tempering treatment, and has certain toughness, plasticity And wear resistance [6].




Figure 10. Bottom plate.

ii. Support Plate

The design of the support plate is shown in Figure 11. The part is connected to the workpiece, the bottom plate, the bolt, the nut and the screw for positioning and clamping of the workpiece. The material of the support plate is 45# medium carbon quenched and tempered structural steel. After quenching and tempering treatment, it has high strength and good machinability, and has certain toughness, plasticity and wear resistance [7].




Figure 11. Support plate.

iii. Auxiliary Support

The design of the auxiliary support is shown in Figure 12. The part is used for auxiliary positioning of the workpiece and is connected to the ram, the bottom plate and the workpiece. The auxiliary support material selects 45# medium carbon quenched and tempered structural steel, which has high strength and good machinability after quenching and tempering treatment, and has certain toughness, plasticity and wear resistance.




Figure 12. Auxiliary support.

iv. Ejector

The design of the ram is shown in Figure 13, which is connected to the support, the auxiliary support, the handle, and the nut. The top rod material selects 45# medium carbon quenched and tempered structural steel, which has high strength and good machinability after quenching and tempering treatment, and has certain toughness, plasticity and wear resistance.





Figure 13. Ejector.

v. Support

The design of the support is shown in Figure 14. The part is connected to the bottom plate, the ejector pin and the bolt, and is mainly used for auxiliary positioning of the

workpiece. The bearing material selects 45# medium carbon quenched and tempered structural steel, which has high strength and good machinability after quenching and tempering treatment, and has certain toughness, plasticity and wear resistance



- 1: HB217-255
- 2: Unnoted chamfer C1

Figure 14. Support.

3.2. Bearing Housing Drilling Mold

There are 6-φ13 holes on the large surface of the bearing housing. If the scribing is used, the machining efficiency is very low, and the machining accuracy is difficult to guarantee. Therefore, it is considered to design a large surface, a hole and a right angle as the positioning reference. The die-casting machine has 6-φ13 holes on the large surface of the bearing housing.

3.2.1. Bearing Box Body Drilling Tooling Structure

The bearing box body drilling tooling [8] structure is shown in Figure 15: The bearing box body drilling tooling mainly consists of the bottom plate, the support, the drill template, the hinge pin, the pressure plate, the contour pin 1, the drill sleeve φ13×20×40, the stud M20×125, nut M20, screw M20×100, cotter pin φ10×45, stud M20×150, contour pin 2, etc.




Figure 15. Bearing housing mold.

- 1: Base plate 2: Support 3: Drill template 4: Hinge pin 5: Press plate 6: Contour pin 1 7: drill sleeve φ13×20×40 8: stud M20×125 9: nut M20 10: screw M20×100 11: Cotter pin φ10×45 12: Stud M20×150 13: Contour pin 2

3.2.2. Working Principle of Bearing Box Drilling Tooling

Place the bearing box drill on the Z3050 radial drilling machine [9] table, press the bottom plate with the pressure plate, clamp the large-faced template of the workpiece, and drill 6- $\phi 13$ holes through the drill sleeve [10].

By using the self-designed bearing housing body to mold the bearing housing 6- $\phi 13$ hole, to meet the dimensional accuracy requirements of the drawings, to ensure the consistency of mass production, solve the problem of low processing efficiency, improve the ergonomics And various performance indicators.

3.2.3. Main Parts Design of Bearing box Drilling Tooling

i. Backplane

The design of the bottom plate is shown in Figure 16. The part is connected with the workpiece, the support, the contour pin 1, the contour pin 2, the screw and the stud, and is the basic component of the tooling. Since the contour pin $\phi 33k6$ is a positive tolerance, the cooperation of the bottom plate and the contour pin is an interference fit. Since the surface roughness of the 4- $\phi 33H7$ holes is 3.2, the process arrangement requires reaming [11]. The material of the bottom plate is selected from 45# medium carbon quenched and tempered structural steel [12], which has high strength and good machinability after quenching and tempering treatment, and has certain toughness, plasticity and wear resistance.




Figure 16. Bottom plate.

ii. Support

The design of the support is shown in Figure 17. The parts are connected to the workpiece, the bottom plate, the drill template, the hinge pin, the bolt, the nut, the screw [13], and the like. There are $\phi 20H7$ holes in the design of the support. Since the outer precision of the hinge pin is negative tolerance, the cooperation between the support and the hinge pin is a clearance fit. The surface roughness of the $\phi 20H7$ hole is 3.2, and the process needs to arrange fine boring. The HT200 gray cast iron parts are selected for annealing treatment, and the blanks are required to have no casting defects such as porosity and shrinkage to ensure the bearing has certain mechanical strength and vibration damping.




Figure 17. Support.

iii. Drill Template

The design of the drill template [14] is shown in Figure 18, which is connected to the support, the hinge pin, the pressure plate, and the drill sleeve. Since the hinge pin $\phi 20g6$ is a negative tolerance, the fit of the drill template and the hinge pin is a clearance fit to facilitate the rotation of the drill template; since the 6- $\phi 20H7$ hole is connected to the drill sleeve, and the outer tolerance of the drill sleeve is a positive tolerance, the drill template is drilled. The fit with the drill sleeve is an interference fit. Since the surface roughness of the $\phi 20H7$ and 6- $\phi 20H7$ holes is 3.2, the process arrangement requires reaming or fine boring. The drilling template material selects 45# medium carbon quenched and tempered structural steel, which has high strength and good machinability after quenching and tempering treatment, and has certain toughness, plasticity and wear resistance.





Figure 18. Drill Template.

iv. Hinge Pin

The design of the hinge pin [15] is shown in Figure 19, which is connected to the support, the drill template, and the split pin. The hinge pin is designed with a tolerance of $\phi 20g6$ outer circle. The size of the support and the drill template hole is $\phi 20H7$, so the fit of the hinge pin to the support and the drill template is clearance fit. The surface roughness of $\phi 20g6$ is 3.2, and the process needs to be ground. The hinge pin material selects 45# medium carbon quenched and tempered structural steel, which has high strength and good machinability after quenching and tempering treatment, and

has certain toughness, plasticity and wear resistance.



HB217-255

Figure 19. Hinge pin

v. Platen

The design of the pressure plate is shown in Figure 20. This part is used for the compression of the drill template, and is connected to the drill template, the contour pin and the nut. The pressure plate material selects Q235-A ordinary carbon steel, which is economical.






Figure 20. Pressure plate.





HB217-255

Figure 21. contour pin 1.

vi. Contour Sales 1

The design of the contour pin 1 is shown in Figure 21. The part is a transitional part connected to the bottom plate and the pressure plate. The contour pin design is marked with a $\phi 33k6$ outer circle tolerance, and the bottom plate $\phi 33H7$ hole is matched with an interference fit. The surface roughness is 3.2,

so the process arrangement needs to be ground. The contour pin 1 material selects 45# medium carbon quenched and tempered structural steel, which has high strength and good machinability after quenching and tempering treatment, and has certain toughness, plasticity and wear resistance.



HB217-255

Figure 22. Contour pin 2.

vii. Contour 2

The design of the contour pin 2 is shown in Figure 22. The part is a transitional part connected to the bottom plate and the drill template. The contour pin design is marked with a $\phi 33k6$ outer circle tolerance, and the bottom plate $\phi 33H7$ hole is matched with an interference fit. The surface roughness is 3.2, so the process arrangement needs to be ground. Contoured pin 2 material selects 45# medium carbon quenched and tempered structural steel, which has high strength and good machinability after quenching and tempering treatment, and has certain toughness, plasticity and wear resistance.

4. The Conclusion

After the preparation of the process specification and the installation of the fixtures, the machining accuracy of the bearing housing is improved, the problem of machining and drilling of the bearing housing is solved, the processing load of the operator is reduced, the labor intensity is reduced, and the work is shortened. The production cycle greatly increases productivity and guarantees product quality.

References

[1] Wang Shaojun. Mechanical Manufacturing Process Design Handbook. Harbin Industrial Press.

- [2] Shanghai Diesel Engine Process Equipment Research Institute. Metal Cutting Machine Tool Fixture Design Manual. Mechanical Industry Press.
- [3] Shanghai Science and Technology Press, Northeast Heavy Machinery Institute, Luoyang Branch. Machine Tool Fixture Design Manual.
- [4] Shen Xueqin. Tolerance coordination technology measurement. Higher Education Press.
- [5] Wu Zongze, Luo Shengguo. Mechanical Design Course Design Manual. Higher Education Press.
- [6] Zhang Jie, Li Xianmin, Zhao Hu. Technical basis of mechanical manufacturing. Southwest Jiaotong University Press.
- [7] Liu Hongwen. Materials Mechanics. Higher Education Press.
- [8] Huang Heting, Wang Furong, Liu Jianming. Mechanical Manufacturing Equipment. Mechanical Industry Press.
- [9] Qiu Xuanhuai. Mechanical Design. Higher Education Press
- [10] Li Yimin. Concise manual for mechanical manufacturing process design. Mechanical Industry Press.
- [11] Ai Xing, Xiao Shigang. Concise Handbook of Cutting Amount. Mechanical Industry Press.
- [12] Design Manual for Mechanical Engineers. Chemical Industry Press.
- [13] Sui Hongjun Wu Runyan. The latest practical hardware manual. Henan Science and Technology Press.
- [14] Lv Yingbo. Manual of Mechanical Drawing. Chemical Industry Press.
- [15] Zhou Kaiqin. Manual of Mechanical Parts. Higher Education Press.