

Foreword: Flow numerical simulations in textile technologies

Lead Guest Editor: Karel Adamek

VUTS, A. S., Svarovska 619, 460 01 Liberec XI, the Czech Republic

Email address:

karel.adamek@vuts.cz

To cite this article:

Karel Adamek. Foreword: Flow Numerical Simulations in Textile Technologies. *International Journal of Mechanical Engineering and Applications*. Special Issue: Moving Forward to Monitory Democracy: Citizens Engagement in Scrutinizing Election Process in Indonesian 2014 General Election. Vol. 3, No. 1-1, 2015, pp. 1-4. doi: 10.11648/j.ijmea.s.2015030101.11

Abstract

The monograph presents the overview of typical numerical flow simulations, solved in VÚTS – Center for Research in Machinery in Liberec (former Research Institute of Textile Machines) in the area of fluid mechanics for various technical applications. First of all in textile technologies, as for instance air jet weaving, spinning, drying, permeability, nonwovens etc. System is completed by auxiliary technologies as for instance air conditioning, exhausting, pneumatic transport etc.

Personal Profile of Lead Guest Editor



Name: Karel Adamek

Titles and Degrees

2005	Professor, branch Applied mechanics
1992	Assoc. Prof., branch Machines designing, Fac. of Machinery, Tech. Univ. in Liberec
1982	PhD (CSc.), branch Fluid mechanics and thermo mechanics, Fac. of Machinery, Tech. Univ. in Liberec
1967	MME (Ing.), branch Machines designing, Fac. of Machinery, Tech. Univ. in Liberec

Education

1974 – 1979	Doctoral study, Fac. of Machinery, Tech. Univ. in Liberec
1974 – 1976	Post gradual courses of university pedagogy, state exam, Tech. Univ. in Liberec
1962 – 1967	Fac. of Machinery, Tech. Univ. in Liberec, spec. Machines designing

Summary of Employment

2006- ...	Research worker at Research Dept. Numerical simulations at VÚTS Liberec, Inc.
1995 – ...	Assoc. Prof., later Prof. at Dept. of Power Equipment, Fac. of Machinery, Tech. Univ. in Liberec (part time)
2002 – 2006	Head of the Dept. of Flow Numer. Simul. at VÚTS Liberec

1984 – 2002	Research worker at Research dept. of weaving engineering at Elitex KVÚ Liberec, later VÚTS Liberec Inc.
1981 – 1984	Looms designer - Elitex k. p. Chrastava
1975 - 1980	Technical lectures at Energy Institute for State Energy Inspection
1970 – 1980	Lecturer at dept. of power equipment, Fac. of Machinery, Tech. Univ. in Liberec
1967 – 1970	Designer of truck motors Škoda - LIAZ n.p. Jablonec n. N., military service

Editorial Group

Lead Guest Editor:

Karel Adamek, VUTS Liberec, Czech Rep., Dept. of flow numerical simulatins, karel.adamek@vuts.cz

Guest Editors:

Jan Kolar, VUTS Liberec, Czech Rep., Dept. od flow numerical simulations, jan.kolar@vuts.cz

Pavel Peukert, VUTS Liberec, Czech Rep., Dept. of flow numerical simulations, pavel.peukert@vuts.cz

Stanislav Juklíček, VÚTS Liberec, Czech Rep., Dept. of informatics, stanislav.juklicek@vuts.cz

Acknowledgments

This overview summary publication was created under the support of the Czech grant No. LO 1213 - Excellent machinery research.

Content

	Page
Foreword <i>Karel Adamek</i>	1
Main weaving nozzles (ejectors) <i>Karel Adamek, Jan Kolar, Jaroslav Pelant, Jan Šimák, Simone Gramsch</i>	5
Relay nozzles and weaving reed <i>Karel Adamek, Petr Karel, Jan Kolar, Václav Kopecký, Slavomír Jirků, Jaroslav Pelant</i>	13
Air conditioning <i>Karel Adamek, Jan Kolar, Pavel Peukert, Marek Kašpar</i>	22
Wall flows <i>Karel Adamek, Dušan Čejka, Zdeněk Mečl, Jaroslav Pelant</i>	28
Exhausting, pneumatic transport <i>Karel Adamek, Jan Kolar, Pavel Peukert, Martin Pustka, Petr Půlpán, Aleš Průšek, Radim Foldyna,</i>	33
Air permeability, drying, blowing <i>Karel Adamek, Jaroslav Fábera, Milan Stejskal, Antonín Havelka, Stanislav Franc</i>	40
Flow numerical simulation in various technologies <i>Karel Adamek, Jan Kolar, Pavel Peukert, Jozef Kaniok, Jiří Štorek, Marcel Havrda, Jaroslav Pelant, Martin Kyncl,</i>	47
Conclusion <i>Karel Adamek</i>	53

Foreword

VÚTS, former Research Institute of Textile Machines was established in Liberec in the year 1951 and it is permanently widely engaged in the research of textile machines. Let us to remind two examples, only:

The first air jet loom prepared for serial, it means the mass production (as the maximum of 5000 pieces per year), was designed in our institute.

The first principle and function model of the open end spinning was designed in our institute, too, and later transferred to the producer.

Both systems, based on air flows, are today used worldwide as standard, modern, reliable, efficient and powerful technologies.

Our small department of numerical flow simulations is engaged in many branches of industry now.

Using of air flow arising either by expansion of compressed air or driven by a fan is very spread in many branches of industry. From the physical principle, it is well-known that energy consumption for air compression is an important item in the total energy balance of operated equipment. Endeavour of its better efficiency is connected with the research of conversion of internal energy compressed air into kinetic energy of air flow. Such conversion is the main operation phenomenon for different kinds of technical equipment. The following text describes some results of air flow research made by numerical modeling, at first in principal parts of air jet weaving system; further of other textiles technologies and some examples from others branches of processing technologies, too.

In connection with the development of calculating methods of finite elements (or volumes) in fluid mechanics and that of computers with an adequate output, too, it is possible to execute numerical modeling of flows now, as a complement or replacing of former experiments. It is clear that every model is an approach to the reality, only, and that it is necessary to verify such results of numerical modeling by experiments or by real operation trials.

In Research Institute for Textile Machines in Liberec/CZ (VÚTS), there has been used a program [1] since 1994 for numerical modeling of two-dimensional (2D) compressible inviscid flows, based on a numerical solution of Euler's equations system, converted from a modeling flow of water steam. Its application is fully competent for a modeling of quick air flow processes in the branch of air jet looms, as for instance expansion and flow of compressed air in weaving nozzle because the compressibility influence is here more important in comparison with viscous friction. In many solved cases, it was demonstrated that it is often possible to use this program to obtain quickly and simply some qualitative knowledge about the systems with expressively slower flows, too, where it should be more correct to use any procedure considering flow viscosity.

Of course, the solution of axis-symmetrical cases

converted into a solution of flat models is not fully correct, too. It is necessary to say that using of results is possible as qualitative ones, only. But as the first imagination for a designer and help for his next designing actions, the influence of this simple method is very positive.

Since 1999 the program [2] has been used, too, for numerical modeling of three-dimensional (3D) viscous compressible flows. The program was developed in Aeronautical Research and Test Institute in Prague/CZ (VZLÚ) for special cases when simple modeling is not adequate. It is based on the numerical solution of Navier-Stokes' equations system. Its application gives the solutions closer to the reality, by the reason that it contains simultaneous influence of compressibility and viscosity of flowing medium. But the extent of the solved models is so large that their application was limited by output of at the time existing personal computers PC (level of the year 2000). That is why, it was necessary to do expressive simplifications of complicated model geometry so that the model more exact with respect to the thermodynamic and physical qualities of medium becomes less exact with respect to its geometry.

As an option, it was used the program [3] developed in VZLÚ, too, for solutions of compressible viscous flow in axis-symmetrical channels, as the checking method for some cases, initially solved as flat (2D) cases. Using the symmetry condition, the extent of spatial (3D) model is similar to flat (2D) one and time of solution is substantially decreased. Generally, we can state that in the images of the flow field of the cases solved by both methods there are some differences, but the global character of the received flows is quite similar.

As time goes on, the commercial program was used for numerical flow simulations, together with the development of in-house procedures.

Procedures of solution are similar as follows: As to the computational mesh density, it should be the highest to get a maximum detailed flow field, but simultaneously the solution time is increasing. From the thermodynamic conditions, defined usually as a pressure ratio between inlet and outlet with corresponding temperatures, the flow /velocity in the modeled area is arising. The presented flow fields (usually as velocity or Mach number isolines) give the best image about the flow qualities in the solved or observed area.

The scales used for individual presented flow fields are different to get an optimum image about it. Due to place saving, the scales are always missing. In general, the smallest value is blue/violet and the greatest one is red, identically with the wave lengths of color components of white light.

From our experience, it is possible to state that for technical practice (design, technology, etc.) it is not necessary to get a mathematically exact solution of the problem. To understand the problem and to determine the next process of the solution it is usually sufficient to determine the influence of a certain parameter in a modeled system on their operation, efficiency, reliability, etc.

The publication contains several papers focused on important or typical themes. Regarding the extent of the

submitted texts, some main received results are shortly described, only, in the form of flow field images completed by their short discussion, eventually, it is indicated the reason and manner of individual application. A more detailed analysis of results is contained in several research reports and published contributions, some of them are quoted in references at the end of each paper.

From the presented theoretical results and from their technical applications results that the numerical simulations of flow and those of heat exchange are very useful instruments when solving tasks from the technical practice, first of all, in two basic areas:

a) Numerical model is able to confirm or refuse with sufficient accuracy a new hypothesis of the solution for a new technical problem.

b) Numerical model enables to display the behavior of an existing monitored system, to indicate a possible reason of its wrong functioning and to indicate the procedure of its remedy.

In both cases, it is not necessary to produce and test time and money demanding testing equipment, to adapt them and to test them again. Numerical simulations give the right direction of the solution; the necessary experimental verification is carried out on the optimal model, only, which, on the basis of performed simulation could be probably the best for realization.

Next papers present several typical areas, where the numerical simulations were used and their results were applied. Of course, it is not any complete overview of problems.

References

- [1] M. Šejna: Software "CoChem Flow", PC Progress Praha, 1994
- [2] J. Pelant: Software "3D weaving channel", VZLÚ Praha, 1999
- [3] Pelant, J.: Software "OsoSym", VZLÚ Praha, 2000